


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁷ : H04R 3/04</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/14998 (43) International Publication Date: 16 March 2000 (16.03.00)</p>
<p>(21) International Application Number: PCT/EP99/06419 (22) International Filing Date: 31 August 1999 (31.08.99) (30) Priority Data: 98202998.5 8 September 1998 (08.09.98) EP (71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (72) Inventors: DE POORTERE, Gerrit, F., M.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). POLISSET, Catherine; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). AARTS, Ronaldus, M.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). (74) Agent: SCHOENMAKER, Maarten; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).</p>		<p>(81) Designated States: CN, JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: MEANS FOR BASS ENHANCEMENT IN AN AUDIO SYSTEM



(57) Abstract

To improve the perceived audio signal it is known to use a harmonics generator to create the illusion that the perceived audio signal comprises lower frequency signal parts than really available. The invention proposes an audio system in which not only the perceived so called ultra bass signals (for example 20 - 70 Hz) are improved but also of the signals in the frequency band between the ultra bass signal and the normal audio signal are created.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

MEANS FOR BASS ENHANCEMENT IN AN AUDIO SYSTEM

The invention relates to an audio system as described in the preamble of claim

1.

The invention further relates to enhancing means.

5 High fidelity reproduction of audio signals ideally requires sound transducers capable of reliably reproducing sounds throughout the listening range of the human beings. This has been determined to be 20-20.000 Hz. However, realistically, most high fidelity speaker systems are capable of reproducing sounds in the frequency range of 40-20.000 Hz. These high fidelity systems include small transducers (tweeters) for reproducing the high end
10 of the frequency range, and relatively large transducers (woofers) for reproducing the low end of the frequency range. Naturally these speaker systems are large in size and take up a substantial amount of space in the listening area.

 However, there are many customers who enjoy high fidelity sound but do not have the space for a high fidelity speaker system. Manufacturers recognizing this problem
15 have been marketing compact audio systems with small speaker systems for these consumers. However in view of the relatively small size of the speaker systems, these small speaker systems are not capable of reproducing audio frequencies in the range of 40-100 Hz. The consumer using these compact audio systems is then able to notice this deficiency and is then disappointed with the system.

20 Such an audio system is known from the European patent application EP-A-0546619 (applicants reference PHA40624). Since the invention of the electrodynamic loudspeaker, there is a need for greater acoustical output, especially at low frequencies. Often however, for instance in television sets or portable audio sets, this acoustical output is severely
25 limited by the small size of the loudspeakers. It is known that this dilemma can be solved by using a psycho-acoustic phenomenon often referred to as virtual pitch or missing fundamental, which evokes the illusion of a higher bass-response, while the loudspeaker does not radiate more power at these low frequencies. This illusion can be created by replacing low-frequency tones, which are present in the audio signal but can not be reproduced by a small loudspeaker,

by harmonics of these tones. The harmonics now represent the low-frequency tones, the so-called ultra bass.

In the known audio system a low-frequency band of an audio signal is selected and supplied to enhancing means in the form of a harmonics generator for generating harmonics of the selected signal. The generated harmonics are thereafter added to the audio signal. In this way the low-frequency perception of the audio signal is improved. In the known audio system a full wave rectifier is used as harmonics generator, which generates only even harmonics.

An object of the invention is to further improve the perceived low frequency audio signals.

To this end a first aspect of the invention provides an audio system as defined in claim 1.

By amplifying with amplifying means a second selected part of the audio signal it is possible to amplify part of the bass signal which is not selected for the so called ultra bass. Hereby the perceptions of the part of the audio signals, which are not improved with the harmonics generator, are improved. The ultra bass signals, with for example a frequency range of 20-70 Hz, are improved with the harmonics generator and the part of the audio signal in the range 70-100 Hz is improved by amplifying in the amplifying means.

An embodiment of an audio system according to the invention comprises the features of claim 2.

A series arrangement of the harmonics generator and the amplifying means makes it possible to obtain a further improved perceived audio signal.

An embodiment of an audio system according to the invention comprises the features of claim 3.

By making the amplification factor of the harmonics generator and/or of the amplifying means dependent on the volume of the audio signal a dynamic control of the low frequency part of the audio signal is obtained. For audio signals with little low frequency signals the harmonics generator and the amplifying means can amplify an obtained signal more than for low frequency signals with a higher low frequency signal level. In this way a distortion can be prevented by higher-level low frequency audio signals.

An embodiment of an audio system according to the invention comprises the features of claim 4.

Herewith the possibilities to control the output signal of the enhancing means are further improved.

The invention and additional features, which may optionally be used to implement the invention to advantage, will be apparent from and elucidated with reference to the examples described below hereinafter and shown in the figures. Herein shows:

Figure 1 a schematic embodiment of an audio system of the prior art,

Figure 2 a first schematic embodiment of enhancing means according to the invention.

Figure 3 a second schematic embodiment of enhancing means according to the invention,

Figure 4 a third schematic embodiment of enhancing means according to the invention,

Figure 5 a fourth schematic embodiment of enhancing means according to the invention,

Figure 6 a schematic embodiment of an ultra bass generator according to the invention, and

Figure 7 a fifth schematic embodiment of enhancement means according to the invention.

Corresponding elements will be referred to with corresponding reference signs throughout the figures.

Figure 1 shows a schematic embodiment of an audio system AS1 of the prior art, comprising processing means PM1 and enhancing means EM1. The audio system further comprises an input I1 for receiving an audio input signal i1 and an output O1 for supplying an audio output signal o1 for example to be supplied to loudspeakers (not shown). The processing means and the enhancing means are both coupled to the input for receiving the audio input signal. The outputs of the processing means and of the enhancing means are coupled to respective inputs of summing means SUM1 for summing the processed signals and supplying the combined signal to the output O1.

The operation of the audio system AS1 is as follows. The received input signal i1 is processed in the processing means PM1 as is normally done in an audio system, which is known to the man skilled in the art and needs no further explanation. The enhancing means EM1 will select a frequency range from the input signal i1, which has to be processed

separately, and afterwards being added in the adding means AM1 to the processed signal. The prior art enhancing means comprises a harmonics generator for generating the so-called ultra bass signal.

In the following the operation of the enhancing means according to the invention will be described in more detail with reference to the further figures.

Figure 2 shows a first embodiment of the enhancing means EM2 according to the invention. In this embodiment the enhancing means comprises an ultra bass generator UBG2 having an harmonics generator HG2 coupled via first filter means FM21 to the input of the enhancing means EM2 and coupled via second filter means FM22 to adding means AM2 at the output of the enhancing means. The output of the adding means AM2 can be coupled to the summing means SUM2 of the audio system (not shown, see figure 1). In parallel to the harmonics generator HG2 and the filter means FM21 and FM22 is coupled amplifying means AMM2. The output of the amplifying means is coupled to the other input of the adding means AM2.

The harmonics generator HG2 generates harmonics of the lower frequency range of the signal, for example 20-70 Hz, so-called ultra bass, to improve the perceived low frequency signals.

The amplifying means are implemented to amplify part of the bass signal, which is not handled in the harmonics generator HG2. For example the amplifying means will amplify the signals in the frequency band 70-100 Hz, to improve the perception of that part of the signal, and hereby the total perceived audio signal.

Figure 3 shows a second embodiment of enhancing means EM3 comprising amplifying means AMM3 and an ultra bass generator UBG3 whereby the amplifying means and the ultra bass generator are controlled by a (mechanical) control CM3. The control means supply a control signal cs3 to the amplifying means and to the ultra bass generator for controlling the amplification factor(s) of both in dependence of the amplitude level of the audio input signal. By making the operation of the ultra bass generator and of the amplifying means volume dependent distortion at high input level will be overcome.

Figure 4 shows a third embodiment of enhancing means EM4 comprising a series-arrangement of an harmonics (for example ultra bass) generator UBG4 and dynamic bass enhancement means DBEM4 as amplifying means.

The signal is supplied to the ultra bass generator UBG4 for generating harmonics of the low frequency signal part. The output of the UBG4 is supplied to adding means AM4 that receives at the other input the input signal i4. The combined signal is

supplied to the so-called dynamic bass enhancement means DBEM4 for amplifying the received signal in dependence of the volume of the signal. Hereby a distortion of the output signal by a high-level low frequency signal will be further overcome.

Figure 5 shows a fourth embodiment of enhancing means EM5 comprising dynamic bass enhancement means DBEM5 (as amplifying means) and the ultra bass generator UBG5 (as harmonics generator) in parallel. The outputs are coupled to adding means AM5 for adding these output signals. The output of the adding means is supplied to SUM5 (see figure 1). Further this output signal is supplied to bass generator energy control means BM5 for detecting the energy of the bass signal and to supply a first control signal cs51 to the dynamic bass enhancement means DBEM5 and a second control signal cs52 to the ultra bass generator UBG5. The bass energy means BM5 also receives the output signals of the dynamic bass enhancement means DBEM5 and of the ultra bass generator UBG5 as inputs. Hereby the performance of the enhancement means is further improved.

Figure 6 shows an embodiment of an ultra bass generator UBG6 (as harmonics generator), whereby the generated ultra bass signal depends on the received input signal and the generated ultra bass signal is added in adding means AM6 to the input signal. Hereby the harmonics generator is made (input) signal dependent.

Figure 7 shows a fifth embodiment of enhancing means EM7 comprising a series-arrangement of an so called infra bass generator IBG7 and so called the ultra bass generator whereby the output signal of the ultra bass generator UBG7 is added in the adding means to the input signal. An infra bass generator creates lower signal frequencies than are available in the input signal, whereas the ultra bass generator creates harmonics of the lower frequency input signal to create the illusion of lower frequencies than the input signal has.

It is to be noticed that above the invention has been explained on the basis of some embodiments. The different embodiments can be combined to obtain the different advantages. For example is it possible to combine the embodiment of the ultra bass generator UBG6 (figure 6) with the embodiment of the enhancement means (for example figure 5).

CLAIMS:

1. Audio system comprising an input for receiving an audio signal and an output for supplying an output signal, processing means for processing the received audio signal and enhancing means, whereby the enhancing means comprise selecting means for selecting a part of the audio signal, and an harmonics generator for generating harmonics of the selected part
5 of the audio signal,
characterized in that the enhancing means further comprise amplifying means and second selecting means for amplifying a second selected part of the audio signal.
2. Audio system as claimed in claim 1, characterized in that the enhancing means
10 comprises a series arrangement of the harmonics generator and the amplifying means.
3. Audio system as claimed in claim 1, characterized in that the harmonics generator and/or the amplifying means are coupled to controlling means which controlling means are adapted to supply a control signal in dependence of the volume of the audio signal.
15
4. Audio system as claimed in claim 1, characterized in that the amplifying means and the harmonics generator are coupled in parallel, the respective outputs are coupled to inputs of adding means, and to control means for detecting and controlling the output signals of the harmonics generator and of the amplifying means.
20
5. Enhancing means for use in an audio system as claimed in claim 1.

1/3




FIG. 1




FIG. 2

2/3




FIG. 3




FIG. 4




FIG. 5

3/3




FIG. 6




FIG. 7

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/06419

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04R3/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04R H03G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 42789 A (PHILIPS ELECTRONICS NV ;PHILIPS NORDEN AB (SE)) 13 November 1997 (1997-11-13)	1,5
A	claim 1 page 11, line 28 -page 13, line 7; figure 9	2-4
A	EP 0 546 619 A (KONINKL PHILIPS ELECTRONICS NV) 16 June 1993 (1993-06-16) cited in the application page 3, line 3 - line 45; figures	1-5
A	US 4 790 014 A (WATANABE KOJI ET AL) 6 December 1988 (1988-12-06) column 1, line 21 -column 2, line 27; figures	1-5
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

*** Special categories of cited documents :**

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

21 December 1999

Date of mailing of the international search report

24/01/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Gastaldi, G

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/06419

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 729 287 A (MATSUSHITA ELECTRIC IND CO LTD) 28 August 1996 (1996-08-28) page 4, line 29 -page 5, line 15; figures	1-5
A	US 5 771 296 A (UNEMURA TOYOAKI) 23 June 1998 (1998-06-23) column 2, line 40 -column 3, line 56; figures	1-5

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/06419

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9742789	A	13-11-1997	CN 1193450 A	16-09-1998
			EP 0843951 A	27-05-1998
			JP 11509712 T	24-08-1999
EP 0546619	A	16-06-1993	DE 69227091 D	29-10-1998
			DE 69227091 T	20-05-1999
			JP 5328481 A	10-12-1993
US 4790014	A	06-12-1988	JP 63204900 A	24-08-1988
			JP 7022437 B	08-03-1995
			JP 62232298 A	12-10-1987
			JP 2011846 C	02-02-1996
			JP 7048919 B	24-05-1995
			JP 63043500 A	24-02-1988
			JP 63102493 A	07-05-1988
			JP 63164794 A	08-07-1988
			CA 1282344 A	02-04-1991
			DE 3782959 A	21-01-1993
			EP 0240286 A	07-10-1987
EP 0729287	A	28-08-1996	JP 8237800 A	13-09-1996
			CA 2170470 A	28-08-1996
			CN 1135120 A	06-11-1996
			US 5668885 A	16-09-1997
			US 5923766 A	13-07-1999
US 5771296	A	23-06-1998	CN 1130329 A	04-09-1996
			JP 8196000 A	30-07-1996

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)